

TECHNICAL DATA

PLS 3R, 3G, 5R, 5G

Point Lasers





Accuracy

Layout right the first time, every time. PLS 3R, 3G and the PLS 5R, 5G are accurate to ≤1/8 in at 30 ft. (≤3 mm @ 10 m)



Pendulum Lock

The PLS 3R, 3G and PLS 5R, 5G are equipped with a pendulum lock, ensuring safe transport and the ability to lock the laser level in tilt mode.



IP54

IP 54 rating to limit dust and water entry for years of operation on the job site.



Li-lon (optional)

Lithium-Ion battery



IEAN

PLS laser levels are backed by a three-year best-in-class warranty, ensuring you don't lose any time on the job. If you experience issues with your PLS tools during the warranty period, except for obvious misuse or damage, your local dealer can provide you a same day replacement tool.

Level. Layout. Build.™

The new PLS 3 and PLS 5 red and green laser levels offer the durability and precision you expect from PLS, a Fluke Company. Our new laser level platform offers a pendulum lock platform for safe transport and tilt mode functionality. The fast settling, self-leveling pendulum gives you accurate points almost instantly.

PRODUCT OVERVIEW

All laser level models

- Accuracy: ≤1/8 in at 30 ft. (≤3 mm @ 10 m)
- Durable pendulum lock platform.

PLS 3R, PLS 3G

- This professional self-leveling three-point red and green laser level allows for fast, accurate layout of reference points and is excellent for steel stud framing, HVAC installation, electrical and residential construction.
- The PLS 3G green beam laser is up to three times brighter than the PLS 3R red beam, making it ideal for projects over longer distances or with lower lighting.
- Kit includes floor stand and L-bracket for fast, easy overhang and centerline measurements.

PLS 5R, PLS 5G

- The PLS 5 is a self-leveling, five-point red and green laser level (plumb, level, and square horizontal and vertical points) equipped for multiple applications.
- Kit includes PLS Pendulum Target, floor stand and L-bracket for fast, easy overhang and centerline measurements.

PLS, The Professional Standard— Built by contractors for contractors

PLS lasers provide bright, crisp reference points and lines for quick and accurate layout. As the Professional Standard of laser levels, PLS tools were developed out of necessity by professional contractors with over 50 years of experience in commercial and residential interior and exterior layout. Now, as a Fluke Company, PLS has incorporated Fluke's high standards for accuracy, ruggedness, and dependability.





Specifications

Openications	PLS 3R, 3G	PLS 5R, 5G
Battery		Alkaline IEC LR6
AA Alkaline Battery Life, Continuous Use		
Red	≥ 30 hours	≥ 20 hours
Green	≥ 16 hours	≥ 9 hours
RBP5 Li-Ion Battery		
Li-Ion Battery Life, Continuous Use		
Red	≥ 100 hours	≥ 70 hours
Green	≥ 45 hours	≥ 25 hours
Point Laser Direction	90° up, down, forward	90° up, down, left, right, forward
Working Range	≤ 30 m (100 ft.)	
Accuracy	≤ 3 mm @ 10 m (≤ 1/8 in at 30 ft.)	
Laser Leveling		
System	Automatic, Pendulum	
Range	4 °	
Point Laser Diameter	≤ 4 mm at 5 m	
Temperature	'	
Operating	-10 °C to 50 °C (14 °F to 122 °F)	
Storage	15 cm x 9 cm x 3 cm (6 in x 3.6 in x 1.3 in)	
With Batteries	-18 °C to 50 °C (-0.4 °F to 122 °F)	
Without Batteries	-20 °C to 70 °C (-13 °F to 158 °F)	
Relative Humidity	0 % to 90 % (0 °C to 35 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 45 % (40 °C to 50 °C)	
Size (H x W X L)	116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in)	
Weight	~0.6 kg (1.3 lb.)	
Safety	IEC 61010-1: Pollution Degree 2	
Laser	IEC 60825-1:2014 Class 2	
Light Source	Semiconductor laser diode	
Max Output Power	< 1 mW	
Wavelength		
Red	635 nm ± 5 nm	
Green	525 nm ± 5 nm	
Electromagnetic Compatibility (EMC)		
	IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B	
	Group 1: Equipment has intentionally generate frequency energy that is necessary for the intentional frequency energy that is necessary frequency energy that is necessary from the intentional frequency energy that is necessary from the intentional frequency energy ene	ernal function of the equipment itself.
International	Class B: Equipment is suitable for use in dom directly connected to a low voltage power sur for domestic purposes.	oply network which supplies buildings used
	Emissions that exceed the levels required by onected to a test object	CISPR 11 can occur when the equipment is con-
Korea (KCC)	Class B Equipment (Broadcast communications equipment for home)	
USA (FCC)	47 CFR 15 subpart B. This product is considered an exempt device per clause 15.103.	





ORDERING INFORMATION

PLS 3G (tripod not included)

Laser Levels				
Part Number	SKU	Item Description	In the Box	
5009340	PLS 3R Z	3-Point Red Laser Bare Tool	PLS 3R laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS FS Floor Stand, Safety Sheet and Quick Reference Guide	
5009357	PLS 3R KIT	3-Point Red Laser Kit	PLS 3R laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS FS Floor Stand, PLS MLB Magnetic L-Bracket, PLS RRT4 Red Reflective Target, Safety Sheet and Quick Reference Guide	
5009369	PLS 3G Z	3-Point Green Laser Bare Tool	PLS 3G laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS FS Floor Stand, Safety Sheet and Quick Reference Guide	
5009378	PLS 3G KIT	3-Point Green Laser Kit	PLS 3G laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS FS Floor Stand, PLS MLB Magnetic L-Bracket, PLS GRT4 Green Reflective Target, Safety Sheet and Quick Reference Guide	
5009384	PLS 5R Z	5-Point Red Laser Bare Tool	PLS 5R laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS FS Floor Stand, Safety Sheet and Quick Reference Guide	
5009391	PLS 5R KIT	5-Point Red Laser Kit	PLS 5R laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS FS Floor Stand, PLS MLB Magnetic L-Bracket, PLS PT Pendulum Target, PLS RRT4 Red Reflective Target, Safety Sheet and Quick Reference Guide	
5009406	PLS 5G Z	5-Point Green Laser Bare Tool	PLS 5G laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS FS Floor Stand, Safety Sheet and Quick Reference Guide	
5009414	PLS 5G KIT	5-Point Green Laser Kit	PLS 5G laser level, PLS canvas pouch, PLS BP5 alkaline battery pack, PLS FS Floor Stand, PLS MLB Magnetic L-Bracket, PLS PT Pendulum Target, PLS GRT4 Green Reflective Target, Safety Sheet and Quick Reference Guide	
Accessories				
4792193	PLS-60573	PLS Pouch, Canvas	PLS Canvas Pouch	
5031929	PLS FS	Floor Stand for PLS 3, 5, 6	PLS FS Floor Stand	
5031934	PLS MLB	Magnetic L-Bracket, PLS 3, 5, 6, 180	PLS MLB Magnetic L-Bracket	
5031952	PLS BP5	BP5 Alkaline Battery Pack	PLS BP5 Alkaline Battery Pack	
5022629	PLS RRT4	Red Magnetic Reflective Target	RRT4 red reflective target	
5022634	PLS GRT4	Green Magnetic Reflective Target	GRT4 green reflective target	
4985124	PLS C18	Laser Level Hard Case	PLS C18, Laser Level Hard Case	
4844979	PLS-10090	Pendulum Layout target, PLS 5	Pendulum Layout target for PLS 5R and PLS 5G	
5214798	PLS HC20	HC20 Line Level Hard Case	Hard Case for all dot line lasers	
5023322	PLS RBP5	Li-lon battery for PLS hand-held lasers with charging cord and adapters	Li-lon battery for PLS hand held lasers complete with charging cord and adapters	



Pacific Laser Systems, A Fluke Company PO Box 9090, Everett, WA 98206

Fluke Europe B.V. PO Box 1186, 5602 BD Eindhoven, The Netherlands

For more information, call: In the U.S.A. 1-800-601-4500 Email: plslaser.orders@fluke.com Web access: http://www.plslaser.com

Modification of this document is not permitted without written permission from Fluke Corporation. Specifications are subject to change without notice. ©2020 Pacific Laser Systems, a Fluke Company. 06/2020 6011585d-en