

# Supplement

Title: PLS180 Green Beam Operators

Supplement

Issue: **3**

Part Number: 4790469

Issue Date: 6/17

Print Date: Aug. 2016

Page Count: 2

Revision/Date:

---

---

This supplement contains information necessary to ensure the accuracy of the above Manual.



© 2017

All rights reserved.

PLS180

Green Beam Operators

Supplement

## Change #1, 589,600

Replace the entire **Specifications** with:

Light source:	Semiconductor laser diode 510-530 nm, visible
Working range:	±100 feet (outdoor w/detector)
Accuracy:	±1/8" @ 30' (<3 mm @ 10 m) As tested: @ 70 °F (± 2°) @ 35 % (±5 %) relative humidity
Leveling:	Automatic
Leveling range	±6°
Power supply:	3AA batteries alkaline or rechargeable
Operating time:	6 hours continuous use with single beam; 2 hours both beams
Operating temp:	0 °F to 122 °F (-18 °C to +50 °C)
Storage temp:	-5 °F to +140 °F (-20 °C to +60 °C)

Supplement	PLS180 Green Beam Operators
Indicator:	Green light: ON Red light: EXCEEDS TILT/ TILT OVERRIDE #4 Amber light: BATTERY LOW
Environment:	Water resistant; not submersible
Dimensions:	2" x 2-7/8" x 3-3/8"
Weight:	10 oz.(0.28kg) (including batteries)
Laser Power:	Class II

## **Change #2, 443**

On the **Feature** page, add:

- Protective Sleeve not shown.